

Addendum-04
CMRL/PHASE-II/SYS/ C3&5 ASA06/2023
27-06-2023

SN	Part	Section	Clause	Original Bidcondition	Revised bidcondition
1.	Part-1	Section – IV	16.5.23	Firewall Throughput should be at least 100 Gbps	Firewall (1@OCC and 1 @ BCC) Throughput should be at least 10 Gbps for OAIT application. Firewall (1@OCC and 1 @ BCC)Throughput should be at least 40 Gbps for FOTS application. Bidder needs to consider Cyber security solution for entire Phase-2 in their design proposal.
2.	Part-2	Section- VI B	16.5.24	Threat Prevention (including FW, IPS, Application Control & Antivirus) throughput must be at least 15 Gbps with real-world / enterprise MIX traffic	NGFW shall provide Threat Prevention (including FW, IPS, Application Control & Antivirus) with real-world / enterprise MIX traffic
3.	Part-2	Section- VI B	16.5.25	NGFW (including FW, IPS, Application Control) throughput must be at least 15 Gbps with real-world / enterprise MIX traffic	Deleted
4.	Part-2	Section- VI B	16.5.26	NGFW should have IPsec VPN throughput of at least 70 Gbps	NGFW shall provide IPsec VPN functionality.
5.	Part-2	Section- VI B	16.5.28	NGFW should support more than 1 Million new sessions per second	Deleted
6.	Part-2	Section- VI B	16.5.29	NGFW should support at least 20 Million concurrent sessions	Deleted
7.	Part-2	Section- VI B	16.5.42	IPS throughput should be at least 15 Gbps or better for Enterprise MIX traffic	NGFW shall provide Intrusion Prevention functionality.